

1. Identification of the substance/mixture and of the company/undertaking:

 Product identifier

 Trade name:
 Penetrant

 Article number:
 BDR - L

 Relevant identified uses of the substance or mixture and uses advised against

 Application of the substance / the preparation

 At the penetration process by colours acc. to EN ISO 3452-1

 [EN 571-1] (DIN 54 152 part 1) for finding surface cracks.

 Details of the supplier of the safety date sheet

Details of the supplier of the safety data sheet Manufacturer/Supplier Helmut Klumpf Technische Chemie KG Industriestr. 15

D - 45699 Herten Phone.: +49(0)2366 1003 - 0 Fax: +49(0)2366 1003 - 11 Email: klumpf@diffu-therm.de **Emergency telephone number:** a.m. or next Emergency phone:

2. Hazards identification

Classification of the substance or mixture

Flammable Aerosol, Category 1 GHS02 Flame

Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labeled according to the CLP regulation.

Hazard pictograms GHS02

Signal word Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Results of PBT and PvB assessment

PBT: Not applicable; vPvB: Not applicable

3. Composition/information on ingredients

Chemical characterization:

Aerosol with mixture of substances listed below and non-hazardous additions.

Components:	Name of chemical	weight %
CAS: 106-97-8	n-butane	5 - 20
EINECS: 203-448-7	GHS02 Flam. Gas 1, H220; GHS04	5 - 20
CAS: 74-98-6	propane	5 - 20
EINECS: 200-827-9	GHS02 Flam. Gas 1, H220; GHS04	5 - 20
CAS: 196823-11-7	oxirane, methyl-, polymer with oxirane, mono isotridecyl ether, block	< 3
EINECS: Polymer	GHS07 Eye Dam./Irrit. 2, H319 signal word: Attention	< 3
CAS: 509-34-2	xanthene dyes C. I. Solvent Red 49	< 2
EINECS: 208-096-8	Acute Tox. 4(oral), H302 S 2, GHS07 Eye Dem./Irrit. 2, H319, H411	< 2

4. First aid measures

General information:

Remove contaminated soaked clothing immediately.

After inhalation:

In the event of symptoms refer for medical treatment.



After skin contact:

In case of contact with skin wash off with soap and water.

After eye contact:

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

After swallowing

Rinse out mouth and then drink plenty of water. Do not induce vomiting. Seek immediate medical advice.

5. Fire fighting measures

Suitable extinguishing material:

ABC powder, foam, carbon dioxide.

Extinguishing material that must not be used for safety reasons: Full water jet.

Special exposure hazards extinguishing from the substance or

preparation itself, combustible products or resulting gases: None

Special protective equipment for fire fighters: None

Additional information's:

Cool containers at risk with water spray jet. Danger for bursting of aerosols when heated for more than 50°C. Aerosols that burst in fire can be mightily shot away.

6. Accidental release measures

Personal precautions:

Avoid contact with eyes and skin.

Ensure adequate ventilation.

Do not breathe vapour. Remove all ignition sources. Do not smoke. Avoid sparks.

Environmental precautions:

Do not discharge into the subsoil/soil.

Do not discharge into the drains/surface waters/groundwater.

Methods for cleaning up/taking up:

Take up with absorbent material

(e.g. sand, sawdust, kieselguhr, general-purpose binder).

7. Handling and storage

Handling:

Advice on safe handling:

Provide good room ventilation even at ground level (vapours are heavier than air).

Advice on protection against fire and explosion:

Keep away from sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Storage:

Requirements for storage rooms and vessels:

Filled aerosols must not be exposed to:

- 1. Heating of more than 50°C by sun beams or other heat sources.
- 2. Storage in gates, passages, wells of staircases, buildings, floors, and lofts.
- Keep container in a well-ventilated place.

Advice on storage compatibility:

Do not store together with oxidizing agents.

Further information on storage conditions:

Keep container in a well-ventilated place.



Classification acc. to prescription:

Aerosols (Aerosol containers) (TRG 300) Ordinance on Industrial Safety and Health TRGS 510.

Storage class: 2B

8. Exposure controls and personal protection

Additional advice on system design:

The necessary protection measures and the nature of the technical procedures will vary depending upon potential exposure conditions.

Control measures: To load limits are not exceeded, should be provided adequate ventilation. Use explosion-proof ventilation equipment.

Ingredients with occupational exposure limits to be monitored:

Components with critical values that require monitoring at the workplace:				
111-90-0	Diethylenglycolmonoethylether (< 50%)			
WEL	35 mg/m ³ , 6 ml/m ³ 2(I);AGS, Y			
106-97-8	n-butane (5 - 20%)			
WEL	2.400 mg/m ³ , 1.000 ml/m ³ ; 4(II); DFG			
74-98-6	propane (5 - 20%)			
WEL	1.800 mg/m ³ , 1.000 ml/m ³ ; 4(II); DFG			

Personal protection equipment:

General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end for the work.

Avoid contact with eyes and skin.

Breathing equipment:

If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable.

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Half-face filter respirator Type A.

Hand protection: Neoprene gloves

Eye protection: Tightly fitting goggles

Skin Protection: Light protective clothing.

General protective measures:

Avoid contact with eyes. Do not inhale aerosols.

9. Physical and chemical properties

General Information:

D

Form: Aerosol	Colour: red	Smell: aln	nost odourless	
Data relevant for safety:	(Product without power gas)			
Boiling range:		195 - 230	°C	
Flash point:		94	°C	
Ignition temperature:		320	°C	
Explosive properties:	The Product is not explosive, but			
	may form flammable/explosive vapour-air mixtu		our-air mixture.	
Explosion limits	Lower e.l.:	1,2	Vol.%	
	Upper e.l.:	11,6	Vol.%	
Vapour pressure (20°C):		< 0,7	mbar	
Density (20°C):		0,99	g/cm ³	
Solubility in water (20°C):	completely miscible			
Viscosity (20°C):		6,05	mm²/s	



10. Stability and reactivity

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. Materials to be avoided: Reacts with strong oxidizing agents. Dangerous reactions:

No dangerous reactions known.

11. Toxicological information

Acute Toxicity:

Irritability/Corrosiveness:

Skin: slightly irritant

Eye: slightly irritant

Sensitization:

No sensitization known.

12. Ecological information

Toxicity

Aquatic toxicity:			
111-90-0	Diethylenglycolmonoethylether		
EC 50	1.982 mg/l (Daphnia) (48h/ daphnia magna)		
LC 50	21.400 mg/l (Acute fish toxicity) (Lepomis macrochirus)		

Degree of elimination: OECD 301B E 90% (1)

Bioaccumulative potential Not worth-mentioning accumulating in organisms.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13. Disposal considerations

Product:

Recommendations:

Hand over to authorized disposal agency.

term:

Waste code No.:

Mixture of solvent

EAV: 14 06 03 tex Contaminated packaging:

Recommendations:

Container must be completely emptied and must not be opened by force.

Hand over to authorized disposal agency.

Waste code No.:

EAV: 15 01 10 term: Iron-metal containers with a contaminated rest of the contents

Waste treatment methods

Recommendations

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Disposal must be made according the local authority regulations.

14. Transport information

Land transport

UN-No.:1950Identification:DRUCKGASPACKUNGEN flammableClass: 2Package Group: --Tunnel restriction code: DClassifications code: 5 Fshipment category: 2Labelling of the Package:UN 1950 AEROSOLELabel-no.: 2.1Packing instruction: P 003, MP 9Limited Quantities Only: 1L(Package ≤ 30 kg)



Marine transport IMDG/GGVSee

					Package Group: Marine Pollutant:	Label:	
Proper Shipping Name: Aerosols (Limited Quantities Only) (Package ≤ 30 kg)							
Air transport ICAO-TI and IATA-DGR							

1950 Class/Division: 2.1 UN/ID-No.: Package Group: --, Label: 2.1 Packing inst. Passenger aircraft: 203/Y203 Max. net/Package: 75 kg/30 kg Packing inst. Cargo aircraft: 203 Max. net/Package: 150 kg Proper Shipping Name: Aerosols, flammable

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

Relevant phrases

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.

National regulations

Water hazard class: Water hazard class 2 (Assessment by list): hazardous for water.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16. Other information

These date are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally contractual relationship.

Department issuing data specification sheet:

Contact: Helmut. Klumpf Technische Chemie KG

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent